

und.1 Trakthenbrot's Theorem

tur:und:tra: sec In ?? we defined **sentences** $\tau(M, w)$ and $\alpha(M, w)$ for a Turing machine M and input string w . explanation Then we showed in ?? and ?? that $\tau(M, w) \rightarrow \alpha(M, w)$ is valid iff T started on input w eventually halts. Since the Halting Problem is undecidable, this implies that validity and satisfiability of **sentences** of first-order logic is undecidable (????).

But validity and satisfiability of sentences is defined for arbitrary **structures**, finite or infinite. You might suspect that it is easier to decide if a **sentence** is satisfiable in a finite **structure** (or valid in all finite **structures**). We can improve the proof of the unsolvability of the decision so that it shows this is not the case.

First, if you go back to the proof of ??, you'll see that what we did there is produce a model \mathfrak{M} of $\tau(M, w)$ which describes exactly what machine M does when started on input w . The domain of that model was \mathbb{N} , i.e., infinite. But if M actually halts on input w , we can build a finite model \mathfrak{M}' in the same way. Suppose M started on input w halts after k steps. Take as domain $|\mathfrak{M}'|$ the set $\{0, \dots, n\}$, where n is the larger of k and the length of w , and let

$$\mathfrak{M}'(x) = \begin{cases} x + 1 & \text{if } x < n \\ n & \text{otherwise.} \end{cases}$$

Otherwise \mathfrak{M}' is defined just like \mathfrak{M} . By the definition of \mathfrak{M}' , just like in the proof of ??, $\mathfrak{M}' \models \tau(M, w)$. And since we assumed that M halts on input w , $\mathfrak{M}' \models \alpha(M, w)$. So, \mathfrak{M}' is a finite model of $\tau(M, w) \wedge \alpha(M, w)$ (note that we've replaced \rightarrow with \wedge). We are halfway to a proof: if M halts on input w , then $\tau(M, w) \wedge \alpha(M, w)$ has a finite model. Unfortunately, the "only if" direction does not hold. For instance, if M after n steps is in state q and reads a symbol σ , and $\delta(q, \sigma) = \langle q, \sigma, N \rangle$, then the configuration after $n + 1$ steps is exactly the same as the configuration after n steps (same state, same head position, same tape contents). But the machine never halts; it's in an infinite loop. The corresponding **structure** \mathfrak{M}' above satisfies $\tau(M, w)$ but not $\alpha(M, w)$. (In it, the values of $n + l$ are all the same, so it is finite). But by changing $\tau(M, w)$ suitable we can rule out **structures** like this.

Consider the **sentences** describing the operation of the Turing machine M on input $w = \sigma_{i_1} \dots \sigma_{i_k}$:

1. Axioms describing numbers and $<$ (just like in the definition of $\tau(M, w)$ in ??).
2. Axioms describing the input configuration: just like in the definition of $\tau(M, w)$.
3. Axioms describing the transition from one configuration to the next:

For the following, let $\varphi(x, y)$ be as before, and let

$$\psi(y) \equiv \forall x (x < y \rightarrow x \neq y).$$

a) For every instruction $\delta(q_i, \sigma) = \langle q_j, \sigma', R \rangle$, the **sentence**:

tur:und:tra:
rep-right

$$\forall x \forall y ((Q_{q_i}(x, y) \wedge S_\sigma(x, y)) \rightarrow (Q_{q_j}(x', y') \wedge S_{\sigma'}(x, y') \wedge \varphi(x, y) \wedge \psi(y')))$$

In other words, the same as the corresponding **sentence** in $\tau(M, w)$, except we add $\psi(y')$ at the end. ($\psi(y')$ ensures that the number y' of the “next” configuration is different from all previous numbers $0, \sigma', \dots$)

b) For every instruction $\delta(q_i, \sigma) = \langle q_j, \sigma', L \rangle$, the **sentence**

tur:und:tra:
rep-left

$$\begin{aligned} \forall x \forall y ((Q_{q_i}(x', y) \wedge S_\sigma(x', y)) \rightarrow \\ (Q_{q_j}(x, y') \wedge S_{\sigma'}(x', y') \wedge \varphi(x, y))) \wedge \\ \forall y ((Q_{q_i}(0, y) \wedge S_\sigma(0, y)) \rightarrow \\ (Q_{q_j}(0, y') \wedge S_{\sigma'}(0, y') \wedge \varphi(0, y) \wedge \psi(y'))) \end{aligned}$$

c) For every instruction $\delta(q_i, \sigma) = \langle q_j, \sigma', N \rangle$, the **sentence**:

tur:und:tra:
rep-stay

$$\forall x \forall y ((Q_{q_i}(x, y) \wedge S_\sigma(x, y)) \rightarrow (Q_{q_j}(x, y') \wedge S_{\sigma'}(x, y') \wedge \varphi(x, y) \wedge \psi(y')))$$

Let $\tau'(M, w)$ be the conjunction of all the above **sentences** for Turing machine M and input w .

Lemma und.1. *If M started on input w halts, then $\tau'(M, w) \wedge \alpha(M, w)$ has a finite model.*

tur:und:tra:
lem:halts-sat

Proof. Let \mathfrak{M}' be as in the proof of ??, except

$$\begin{aligned} |\mathfrak{M}'| &= \{0, \dots, n\} \\ \rho^{\mathfrak{M}'}(x) &= \begin{cases} x + 1 & \text{if } x < n \\ n & \text{otherwise,} \end{cases} \end{aligned}$$

where $n = \max(k, \text{len}(w))$ and k is the least number such that M started on input w has halted after k steps. We leave the verification that $\mathfrak{M}' \models \tau(M, w) \wedge E(M, w)$ as an exercise. \square

Problem und.1. Complete the proof of **Lemma und.1** by proving that $\mathfrak{M}' \models \tau(M, w) \wedge E(M, w)$.

Lemma und.2. *If $\tau'(M, w) \wedge \alpha(M, w)$ has a finite model, then M started on input w halts.*

tur:und:tra:
lem:sat-halts

Proof. We show the contrapositive. Suppose that M started on w does not halt. If $\tau'(M, w) \wedge \alpha(M, w)$ has no model at all, we are done. So assume \mathfrak{M} is a model of $\tau(M, w) \wedge \alpha(M, w)$. We have to show that it cannot be finite.

We can prove, just like in ??, that if M , started on input w , has not halted after n steps, then $\tau'(M, w) \models \chi(M, w, n) \wedge \psi(\bar{n})$. Since M started on input w does not halt, $\tau'(M, w) \models \chi(M, w, n) \wedge \psi(\bar{n})$ for all $n \in \mathbb{N}$. Note that by ??, $\tau'(M, w) \models \bar{k} < \bar{n}$ for all $k < n$. Also $\psi(\bar{n}) \models \bar{k} < \bar{n} \rightarrow \bar{k} \neq \bar{n}$. So, $\mathfrak{M} \models \bar{k} \neq \bar{n}$ for all $k < n$, i.e., the infinitely many terms \bar{k} must all have different values in \mathfrak{M} . But this requires that $|\mathfrak{M}|$ be infinite, so \mathfrak{M} cannot be a finite model of $\tau(M, w) \wedge \alpha(M, w)$. \square

Problem und.2. Complete the proof of [Lemma und.2](#) by proving that if M , started on input w , has not halted after n steps, then $\tau'(M, w) \models \psi(\bar{n})$.

tur:und:tra:
thm:trakhtenbrodt

Theorem und.3 (Trakhtenbrot's Theorem). *It is undecidable if an arbitrary sentence of first-order logic has a finite model (i.e., is finitely satisfiable).*

Proof. Suppose there were a Turing machine F that decides the finite satisfiability problem. Then given any Turing machine M and input w , we could compute the sentence $\tau'(M, w) \wedge \alpha(M, w)$, and use F to decide if it has a finite model. By [Lemmata und.1](#) and [und.2](#), it does iff M started on input w halts. So we could use F to solve the halting problem, which we know is unsolvable. \square

tur:und:tra:
cor:jproof-incomp

Corollary und.4. *There can be no derivation system that is sound and complete for finite validity, i.e., a derivation system which has $\vdash \psi$ iff $\mathfrak{M} \models \psi$ for every finite structure \mathfrak{M} .*

Proof. Exercise. \square

Problem und.3. Prove [Corollary und.4](#). Observe that ψ is satisfied in every finite structure iff $\neg\psi$ is not finitely satisfiable. Explain why finite satisfiability is semi-decidable in the sense of ??. Use this to argue that if there were a derivation system for finite validity, then finite satisfiability would be decidable.

Photo Credits

Bibliography